

5

**TITLE OF THE INVENTION**

10 APPARATUS FOR ~~BODY MOTION~~ STEERING CONTROL OF FOR WATER CRAFT BY  
OPERATOR BODY MOTION COMMANDS

**CROSS-REFERENCE TO RELATED APPLICATIONS**

15 This non-provisional patent application claims the benefit of United States Provisional Patent  
Application 60/438,080 filed on January 6, 2003.

**BACKGROUND OF THE INVENTION**

20 **Field of the Invention**

This invention relates to water craft. This invention further relates to an apparatus for ~~body motion~~  
steering control of for water craft by operator body motion commands.

## MARKED UP SPECIFICATION

### Background of the Invention

Water craft with outboard motors are commonly used for recreational fishing in rivers and lakes.


5 The outboard motors are electric or gasoline driven. One type of fishing, called trolling, requires the operation of the outboard motor while fishing. When trolling, the operator is compelled to steer the craft while fishing. Understandably, the operator, holding the fishing rod, will find it difficult to steer the craft and fish at the same time. Prior to my invention, trolling usually required setting the motor in a first desired direction along a first desired track. When the operator desires  
10 to change to a second direction and track, it is necessary to suspend fishing operations and direct full attention to the outboard motor. Clearly, this disruption of fishing operations leads to a lessened enjoyment of the sport.

Therefore, it is desirable to have an apparatus that can be used for trolling that does not require the  
15 disruption of fishing operations to steer the craft.

### OBJECTIVES OF THE INVENTION

It is an object of the present invention to provide an apparatus for ~~body-motion~~ steering control of  
20 a for water craft by operator body motion commands.

It is a further objective of the present invention to provide an apparatus for steering water craft that does not require the operator to suspend fishing operations in order to change the direction of the water craft.



## SUMMARY OF THE INVENTION

In order to overcome the deficiencies noted above and to meet the objectives stated herein, my invention provides for an apparatus for body motion steering control for water craft.

My invention is an apparatus for body motion steering control adapted for installation in a small water craft powered by an outboard motor such as an electric trolling motor or a small gasoline driven motor.

My invention comprises a seat mounted to a first and second swivel permitting rotation of the seat about a first vertical axis. The seat and first and second swivels are mounted to a stationery base platform which is typically a flat hull cross member. The seat is adapted to receive body motion commands from an operator sitting in it.

The seat comprises a generally horizontal seating platform, two side members and a back rest. The seat is contoured for comfort and to allow the operator to better transmit body motion to the seat.

A first control member holds a pin that can engage a second control member. The first control member is mounted to the seat and first swivel. The second control member is mounted between and to the first and second swivel. When the pin is engaged, first swivel is stopped and only the second swivel is free to rotate. The first control member that is fixed to the seat can be, in turn, fixed at a predetermined angle with respect to the second control member to permit the operator to

## MARKED UP SPECIFICATION

~~fish over the port or starboard side of the water craft while remaining generally oriented toward the front of the water craft.~~

~~There is a rod between the second control member and the outboard motor. When the pin is engaged, the rod transfers body motion commands from the seat to the outboard motor through the second control member.~~

My invention is an apparatus for steering control of a water craft by operator body motion commands. The water craft has at least one flat hull cross-member having an upper surface and is propelled by an outboard motor having a first vertical axis. The apparatus comprises a swivel seat for accepting said body steering commands. The seat comprises swivel means for rotation about a second vertical axis and a bottom surface. The swivel seat has a first disengaged mode wherein the body motion commands are not transmitted to the outboard motor; and, a second engaged mode wherein the body motion commands are transmitted to the outboard motor. Also included are means for moving the swivel seat from the first disengaged mode to the second engaged mode and back again to the first disengaged mode. The invention includes means for transmitting the body motion commands to the outboard motor, whereby the body motion commands are translated into steering commands causing the outboard motor to pivot in a desired direction about the first vertical axis.

Swivel means comprises a first swivel co-axial with the second vertical axis and mounted by mounting means to the at least one flat hull cross-member upper surface; and, a second swivel co-axial with the second vertical axis and mounted by mounting means between the first swivel and the bottom surface of the swivel seat.

## MARKED UP SPECIFICATION

- Engagement means comprises a first control member having a first end and a second end. The first control member first end is mounted by mounting means between the first swivel and the swivel seat bottom surface. There is a slotted sleeve fixed to the first control member second end.
- 5 There is also a second control member having a first end and a second end. The second control member first end is mounted by mounting means between the first swivel and the second swivel. The second control member second end has an aperture and this aperture is co-axial with the slotted sleeve. A retractable biased engagement pin is slidably mounted within the slotted sleeve. The pin has an engagement end. The pin further has a first retracted position wherein the
- 10 engagement end of the pin is disengaged from the aperture. This results in the swivel seat being in its first disengaged mode. In the second engaged position, the pin engagement end is engaged with the aperture thereby coupling the first control member to the second control member. This results in the first and second control members rotating dependently so that rotation of the swivel seat about the second vertical axis causes identical rotation of the second control member about
- 15 the second vertical axis.

- Means for transmitting the body motion commands to the outboard motor comprise a connecting rod having a first end and a second end. The first end is connected by first connecting means to the second control member. The second end is connected by second connecting means to the
- 20 outboard motor so that movement of the second control member about the second vertical axis is transmitted by the connecting rod to the outboard motor and translated into sympathetic movement of the outboard motor about the first vertical axis.

## MARKED UP SPECIFICATION

The first swivel comprises a first upper mounting plate, a first lower mounting plate mounted to the hull cross-member upper surface; and, a first circular bearing track disposed between the first lower mounting plate and the first upper mounting plate. The first circular bearing track includes a first plurality of bearings permitting rotation of the first lower mounting plate with respect to the first upper mounting plate. The second swivel is similarly constructed.

Construction of the swivel seat comprises a horizontal seating platform having a left side and a right side. The horizontal seating platform is contoured for receiving the buttocks of an operator. There is also an upward sloping left side member fixed to the left side of the horizontal seating platform. The left side member is adjacent to the left thigh of an operator and contoured to receive the contour of the left thigh of an operator. There is also an upward sloping right side member fixed to the right side of the horizontal seating platform and positioned adjacent to the right thigh of an operator. It is contoured to receive the contour of the right thigh of an operator. The seat includes a backrest fixed to the horizontal seating platform. The backrest is adapted for pivoting adjustment about a horizontal axis for operator comfort.

The first control member comprises a first plate having a longitudinal axis. This first plate has a paddle shape comprising four contiguous and congruent portions: a shaft portion, a throat portion, a blade portion and tip portion. The shaft portion has a first end having a first width, a first side and a second side. The first side and the second side are parallel and the first end is disposed perpendicular between the first side and the second side. The throat portion has a third side and a fourth side that are incurvate. The blade portion has a fifth side and a sixth side that are arcuate. The tip portion is linear and disposed between the fifth side and the sixth side, perpendicular to the longitudinal axis and parallel to the first end. The shaft portion includes an aperture located

## MARKED UP SPECIFICATION

adjacent to the first end and upon the longitudinal axis. The blade portion includes a first elongate aperture having a first aperture longitudinal axis having an angle of about negative 45 degrees from the first control member longitudinal axis. There is a second elongate aperture having a second aperture longitudinal axis having an angle of about positive 45 degrees from the first control member longitudinal axis. The blade portion is mounted between the bottom surface of the swivel seat and the second rectangular upper mounting plate.

The second control member comprises a second flat plate having a second flat plate longitudinal axis, a top surface and a bottom surface. The second flat plate has a substantially keystone shape including a flat bottom side, a lower left corner, a lower right corner, an arcuate top side, a top left corner, a top right corner, a left side inclined away from the second flat plate horizontal axis, and a right side inclined away from the second flat plate horizontal axis. The second control member further includes: a first elongate aperture located proximate to the lower left corner; a second elongate aperture located proximate to the lower right corner; a third aperture located proximate to the left side with a raised collar; a fourth aperture located adjacent to the third aperture and proximate to the left side also having a raised collar; a fifth elongate aperture located proximate to the top left corner; a sixth elongate aperture located proximate to the top right corner; and, a seventh aperture located at the top end of the longitudinal axis of the second control member. The second control member further includes: a first rectangular projection projecting from the top left corner; a second rectangular projection projecting from the middle of the arcuate top surface along the longitudinal axis; and, a third rectangular projection projecting from the top right corner. These are adapted as sighting guides so that an operator can visually guide the pin into engagement with the second control member. The second control member is mounted between the first rectangular upper mounting plate and the second rectangular lower mounting member.

## MARKED UP SPECIFICATION

- Means for transmitting body use motion commands from the seat body to the outboard motor  
comprise: a connecting member having a first threaded end and a second threaded end; means for  
connecting the connecting member first threaded end to the second control member; and, means  
5 for connecting the connecting member second threaded end to the outboard motor. Connecting  
means comprise a bracket comprising: a base having a threaded aperture adapted to receive the  
connecting member first threaded end; a first tine fixed to the base having an first arcuate free end  
in which there is a first tine first aperture. There is also a second tine fixed to the base opposite to  
and parallel to the first tine. The second tine has a second arcuate free end also with an aperture.  
10 The bracket is adapted to receive the left side of the control member between the first and second  
tines. The first tine first aperture and the second tine second aperture are co-axially aligned with  
the control plate third aperture. There is also included a second pin member adapted for releasable  
engagement within the co-axially aligned first tine first aperture, second tine second aperture and  
second control member third aperture thereby fixing the connecting member first end to the second  
15 control member in a pivoting relationship.

- Means for connecting the connecting member second end to the outboard motor comprises a  
bracket similar to the one described above. In addition, there is a bracket arm having a  
longitudinal axis, a first half and a second half. The first half has at least two apertures positioned  
20 vertically and the second half also has at least two apertures positioned vertically. There is one  
threaded longitudinal bore in the bracket arm adapted to receive a threaded rod. A friction clamp  
is clamped around the vertical shaft casing of the outboard motor. It has a collar portion adapted  
to frictionally engage the vertical shaft casing and two adjacent and parallel arms apertured to  
receive the threaded rod. To tighten the friction clamp, there is a throttling nut adapted for



## MARKED UP SPECIFICATION

threaded engagement onto the threaded rod. A pin is used for pinning the bracket first end between the third tine and the fourth tine in a pivoting relationship.

5 Further objects and advantages will become apparent from a consideration of the ensuing description and drawings.

## MARKED UP SPECIFICATION

### DESCRIPTION OF THE DRAWINGS

Figure 1 ~~comprises various views of a water craft using a preferred embodiment of my invention~~  
illustrates a top view of an open water craft having an outboard motor and centered swivel seat and  
5 elements of my invention.

Figure 2 ~~comprises various views of the seat body of one embodiment of my invention. illustrates~~  
a side view of an open water craft having an outboard motor and a centered swivel seat and shows  
the connecting member of my invention between the seat and the outboard motor and the general  
10 location of the first and second swivels of my invention situated below the seat.

Figure 3 ~~is a schematic elevation view the first and second swivel bodies of one embodiment of~~  
~~my invention. is a perspective view of an open water craft having an outboard motor and a~~  
centered swivel seat showing elements of my invention.  
15

Figure 4 ~~is view the pin member of one embodiment of my invention in a first engaged and second~~  
~~disengaged position with respect to the second control member. is a front view of an open water~~  
craft having an outboard motor and centered swivel seat showing elements of my invention.

20 Figure 5 ~~is a view of the pin member of one embodiment of my invention. is a side view of a~~  
swivel seat of the type shown in Figures 1, 2, and 3 showing elements of my invention.

Figure 6 ~~comprises various views of the first control member of a preferred embodiment of my~~  
~~invention. is a top view of the seat shown in Figure 5.~~

## MARKED UP SPECIFICATION

Figure 7 ~~comprises various views of the second control member of a preferred embodiment of my invention.~~ is a front view of the seat shown in Figures 5 and 6 showing elements of my invention.

- 5    Figure 8 ~~is top view of the position of the first control member with respect to the second control member in one embodiment of my invention.~~ is a perspective view of the seat shown in Figures 5, 6 and 7 showing elements of my invention.

- Figure 9 ~~comprises various views of the rod of one embodiment of my invention connecting the second control member to the outboard motor.~~ is a detailed view of the swivels of one embodiment of my invention showing the pin engaged.
- 10

- Figure 10 ~~comprises various views of the clevis of one embodiment of my invention.~~ is a detailed view of the pin disengaged of one embodiment of my invention.
- 15

- Figure 11 ~~shows a view of the positional relationship between the first control member, the second control member and the pin in one embodiment of my invention.~~ is the same view as Figure 10 showing the pin in the engaged position.

- 20    Figure 12 ~~is a detailed view of one clevis of my invention attached to the second control member.~~ is a detailed view of one embodiment of the pin.

## MARKED UP SPECIFICATION

Figure 13 is ~~a view of the connection between another clevis of my invention and the outboard motor.~~ is an illustration showing a top view (A) and a side view (B) of the first control member of one embodiment of my invention.

5    Figure 14 ~~comprises various views of the bracket used in one embodiment of my invention.~~ is a top view (A) and a side view (B) of the second control member of one embodiment of my invention.

Figure 15 ~~is a schematic view of the operation of one embodiment of my invention.~~ is a top view  
10    showing the operating relationship between the first and second control members.

Figure 16 ~~is another schematic view of the operation of one embodiment of my invention.~~  
illustrates three views: A perspective view, B side view, and C top view of the connecting member  
of one embodiment of my invention.

15    Figure 17 illustrates three views: A side view, B top view and C perspective view of the bracket of one embodiment of my invention.

Figure 18 is a detailed view of the connection of a bracket to the second control member of one  
20    embodiment of my invention.

Figure 19 is a detailed view of the connection of a bracket to the connecting arm of one  
embodiment of my invention.

## MARKED UP SPECIFICATION

Figure 20 is an illustration of various views: A frontal view, B top view, C perspective view and D side view of the connecting arm of one embodiment of my invention.

5 Figure 21 is a view of the operation of one embodiment of my invention with the pin member disengaged.

Figure 22 is a view of the operation of one embodiment of my invention with the pin member engaged.

10

## MARKED UP SPECIFICATION

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Figures 1, 2, 3 and 4 my invention shown generally as (10) is an apparatus for ~~body~~  
~~motion~~ steering control of small water craft by operator body motion commands. My invention  
5 (10) is adapted for installation in a small water craft (12) having a hull (14), a bow (16), a stern  
(18), a ~~port~~ left side (20) and a ~~starboard~~ right side (22). The stern includes a transom member  
(24) adapted to mount an outboard motor (26). The outboard motor can be an electric trolling  
motor or a small gasoline driven motor. The motor has a vertical shaft casing (28) in which the  
drive shaft of the motor is contained. The shaft casing rotates about a first vertical axis (29). The  
10 drive shaft is connected by a transmission (30) to a propeller (32). The small craft includes at least  
one flat hull cross-member (34) acting as a seat. The at least one flat hull cross-member (34) has  
an upper surface (38), a first length (40) and a first width (42).

Referring now to ~~Figures 1 and 2~~ Figures 5 to 8, the apparatus of my invention (10) comprises a  
15 swivel seat body (44) having swivel means (45) permitting rotation of the seat ~~body~~ (44) about a  
first second vertical axis (46). The swivel seat body (44) has a bottom surface (81). Swivel  
means (45) is mounted by mounting means to the upper surface of ~~a stationery base platform~~  
~~which is typically the flat hull cross-member (34).~~ Throughout the detailed description of my  
invention ~~the~~ “mounting means” typically comprise a nut, bolt and washer combination ~~although~~  
20 ~~the invention may be permanently fixed by welding to the hull cross-member (34).~~ In another  
embodiment of the invention, the ~~swivel body stationery base platform~~ flat hull cross-member may  
be a separate rectangular member ~~having a width and length similar the width and length of the~~  
~~hull cross-member~~ which can be temporarily and releasably fixed to the hull cross-member (34) by

## MARKED UP SPECIFICATION

temporary mounting means such as clamps. The seat body (44) is adapted to receive body motion commands from an operator as more fully explained below.

~~My invention (10) also includes means, generally shown as (50), for transmitting body motion~~  
5 ~~commands from the seat body (44) to the outboard motor (26). There is also included in my~~  
~~invention (10) means, generally shown as (52) for controlling the swiveling motion of the seat~~  
~~body (44). There is also included in my invention means, generally shown as (54) for translating~~  
~~the body motion commands into outboard motor (26) steering commands.~~

10 The apparatus of my invention has a first disengaged mode wherein the body motion commands of  
the operator are not transmitted to the outboard motor. The apparatus of my invention also has a  
second engaged mode wherein the body motion commands of the operator are transmitted to the  
outboard motor. Engagement means are included for moving the apparatus from the first  
disengaged position to the second engaged position. Means are provided for transmitting body  
15 motion commands of the operator to the outboard motor which cause the outboard motor to pivot  
in the desired direction about the first vertical axis.

~~Still referring to Figures 1 and 2,~~ Still referring to Figures 5 to 8, there is provided a more detailed  
description of the swivel seat body (44) of my invention (10). The swivel seat body (44)  
20 comprises a generally horizontal seating platform (56) having a left side and a right side. The  
seating platform may be contoured to more comfortably accept the buttocks of an operator.  
Alternatively, there may be a cushion fixed to the horizontal seating platform (56) for operator  
comfort. The seating platform (56) has a leading edge (60) having a sinusoidal contour ~~(62)~~ that is  
adapted to comfortable accept the back thighs of an operator and, as well, to facilitate the swivel

## MARKED UP SPECIFICATION

motion of the swivel seat ~~body~~ by providing an abutting surface (at 60) between the legs of the operator for ~~port left~~ and ~~starboard right~~ swivel motions of the swivel seat ~~body~~.

In order to translate body motion of the operator into swivel motion of the swivel seat ~~body~~ (44),  
5 the swivel seat ~~body~~ includes a first upward curving ~~port left~~ side member (64) fixed to the ~~port~~  
left side (65) of the horizontal seating platform (56). The first curving ~~port left~~ side member (64)  
has an inwards concave surface to better fit against the substantially convex contour of the left  
thigh of an operator. The first curving ~~port left~~ side member (64) has a first top surface (68) to act  
as an arm rest and a first skirt (70) depending down from the first arm rest (68). The first skirt (70)  
10 and first top surface (68) create a first hollow (70 71) that may be used for grasping by the  
operator. Similarly, on the ~~starboard right~~ side (22) of the swivel seat ~~body~~ (44) there is a second  
upward curving ~~starboard right~~ side member (72) fixed to the ~~starboard right~~ side (74) of the  
horizontal seating platform (56). The second curving ~~starboard right~~ side member (72) has an  
inwards concave surface to better fit against the substantially convex contour of the right thigh of  
15 an operator. The second curving ~~starboard right~~ side member (72) has a second top surface (74)  
adapted to act as an arm rest and a second skirt (76) depending from the second top surface (74).  
The second top surface (74) and the second skirt (76) act together to form second hollow (78) that  
may be used for grasping by an operator. The swivel seat ~~body~~ (44) further includes a third  
upward curving back member (80) disposed between the ~~port left~~ upwardly curving side member  
20 (64) and the ~~starboard right~~ upward curving side member (72). The upward curving back member  
(80) is adapted to conform to the lower back and buttocks of an operator. The horizontal platform  
(56), ~~port left~~ side member (64), ~~starboard right~~ side member (72) and back member (80) are  
moulded from a suitable thermoplastic material from a single mould and form a single piece. Also



## MARKED UP SPECIFICATION

included as part of the seating body (44) is back rest (82). Back rest (82) is moulded as a single piece from suitable thermoplastic materials and possesses a contour adapted to follow the contour of an operator's back for comfort and to facilitate transmission of body motions to the swivel seat body (44). The bottom of back rest (82) includes a ~~port~~ left projection (84) having an aperture (86) that is adapted to receive a pin in order to pin the ~~port~~ left projection (84) to apertured lug (867) on the upper ~~port~~ left surface (68). The ~~starboard~~ right side is obviously similarly configured but not illustrated in this Figure 28. This permits the backrest (82) to pivot to and fro around a horizontal axis (88).

Referring now to Figure 3 9, there is shown greater detail of the swivel means of my invention.

10 ~~(10) shown generally at (46) that permits the motion of the seat body (44) around first vertical axis (486). Swivel means (46) is~~ The swivels are mounted by mounting means between the bottom surface (81) of the seat body (44) and the upper surface of the flat hull cross member stationary base platform (34). Swivel means comprises a first swivel body (90) co-axial with the first second  
15 vertical axis (486) and a second swivel body (92) also co-axial with the first second vertical axis (46). The first swivel co-axial with the second vertical axis is mounted by mounting means (96) to the at least one flat hull cross-member (34) upper surface. The second swivel co-axial with the second vertical axis is mounted by mounting means (96) between the first swivel and the bottom surface (81) of the swivel seat.

20 Still referring to Figure 9, the engagement means moving the apparatus from a disengaged mode to an engaged mode comprises a first control member (150) having a first end (151) and a second end (153). The first control member first end is mounted by mounting means between the first swivel

## MARKED UP SPECIFICATION

and the swivel seat bottom surface. A slotted sleeve (302) is fixed to the first control member second end. There is also a second control member (200) having a first end (201) and a second end (203). The second control member first end is mounted by mounting means between the first swivel and the second swivel. The second control member second end has a series of apertures (242, 244 and 246) that move with the second control member to be co-axial with the slotted sleeve. In this Figure 9, aperture (244) is under the sleeve. There is also a retractable biased engagement pin (300) slidably mounted within the slotted sleeve. As shown in Figure 10, the pin has an engagement end (309). When the pin is in a first retracted position the pin engagement end is disengaged from the aperture resulting in the apparatus of my invention being in its first disengaged mode. As shown in Figures 9 and 11, when the engagement end of the pin is engaged with the aperture of the second control member the result is the coupling of the first control member to the second control member resulting in the apparatus of my invention being in its second engaged position. The first swivel (90) is free to rotate but the second swivel (92) is not free to rotate. The first and second control members rotate dependently and rotation of the swivel seat about the second vertical axis causes identical rotation of the second control member about the second vertical axis.

The first swivel body (90) comprises a first ~~rectangular~~ lower mounting plate (94) mounted by mounting means (96) to the upper surface of the hull cross-member ~~stationery base platform~~ (34). The first swivel body (90) also includes a first ~~rectangular~~ upper mounting plate (98) and a first circular bearing track (100) disposed between the first lower mounting plate and the first upper mounting plate including a plurality of bearings (102) disposed in the first bearing track. The bearings permit the first ~~rectangular~~ upper mounting plate (98) to rotate with respect to the first

## MARKED UP SPECIFICATION

~~rectangular~~ lower mounting plate (94) fixed to the ~~stationery base platform~~ upper surface of the hull cross-member (34).

5 The second swivel ~~body~~ (92) comprises a second ~~rectangular~~ lower mounting plate (104) mounted by mounting means (96) in a spaced relationship above the first ~~rectangular~~ upper mounting plate (98) of the first swivel ~~body~~ (90). Between mounting plate (104) and mounting plate (98) are shims (106) having a height equal to the height of the second control member (200).

10 There is also a second ~~rectangular~~ upper mounting plate (108) mounted by mounting means (96) in a spaced relationship to the bottom surface (81) of the swivel seat body (44). There are shims (107) mounted between plate (108) and surface (81). The shims have the same height as the first control member (150).

15 The second swivel ~~body~~ (92) also includes a second circular bearing track (110) disposed between the second lower mounting plate and the second upper mounting plate including a plurality of bearings (112) disposed in the second bearing track. The plurality of bearings permit the second ~~rectangular~~ lower mounting plate (104) to rotate with respect to the second ~~rectangular~~ upper mounting plate (98).

20 The four ~~rectangular~~ mounting plates (94), (98), (104) and (108) ~~each have four corners that are~~ apertured to accommodate mounting means (96).

Still referring to Figure 3 9, there is shown detail of the control means, shown generally as (52) for controlling the swivel of the seat body (44). There is a first control member (150) mounted

## MARKED UP SPECIFICATION

between the bottom surface (81) of the seat body (44) and the first rectangular upper mounting plate (108). ~~As more fully explained below, the first control member (150) controls movement of the seat body (44) with respect to the second control member (200). Second control member (200) is mounted between mounting plate (104) and mounting plate (98). There is a third control~~  
5 ~~member pin (300) fixed to the first control member (150) and adapted for engagement with the second control member (200) so as to prevent relative motion between the first and second control members.~~

Referring now to Figures 3, 4 and 5 10 and 11 there is shown additional detail of pin member  
10 (300) disengaged from second control member (200). ~~one embodiment of my invention wherein the third control member~~ Pin member (300) comprises a pin member that is mounted in a sliding relationship within a sleeve (302) fixed to the end of first control member (150). Pin member (300) includes a shaft portion (303), a handle portion (301) and an engagement end (309).

~~Biassing means~~ Spring (304) is included within the sleeve (302) to provide biasing to the pin  
15 member (300). Lugs (305) are fixed to opposite sides of pin member (300) and are adapted to slide up and out of slot (307) in sleeve (302) and rest upon the surface of sleeve (302) to keep pin (300) in a recessed position with spring (304) compressed within the sleeve. Alternatively, the biasing means (303) can be located outside of the sleeve (302) as illustrated in Figure 10.

20 Referring now to Figure 11, pin member (300) is shown in engaged with control member (200) by engagement end (309). Spring (304) is in an expanded position and ensures that pin member (300) remains engaged until the operator lifts the pin out of sleeve (302). The lugs (305) and are within slot (307).

## MARKED UP SPECIFICATION

Referring now to Figure 12, there is shown detail of a preferred embodiment of pin member (300).

Pin member (300) comprises a handle portion (301), a shaft portion (303), an engagement end (309) and two opposite lugs (305) in the shaft of the pin member.

- 5 Referring to ~~Figures 4 and 5~~, there is shown the pin member (300) in a first disengaged position (Figure 4A) and a second engaged position (Figure 4B). The pin member (300) includes a vertical shaft portion (304) having an engagement end (306). Pin member (300) also includes handle portion (308). The vertical shaft portion includes two opposing horizontal projections (309) and (310). The projections are adapted for sliding engagement within slot (314). When the pin
- 10 member (300) is fully engaged into the second control plate (200) as shown in Figure 4B, the horizontal projections (309) and (310) are located at the bottom of the slot (314). The biasing member (304) expands to keep the engagement end (306) within the control member (200). When the pin member is disengaged from control member (200) the projections (309) and (310) are outside of the slot (314) and sit on the top surface (316) of guide member (302). The guide
- 15 member (302) is a tubular structure that is welded into place within control member (150).

- Referring now to Figure ~~6~~ 13, there is shown ~~various views~~ a top view (A) and a side view (B) of first control member (150). The first control member (150) comprises a first flat plate having a longitudinal axis (152). The first flat plate (150) has a paddle shape including four contiguous and
- 20 congruent portions comprising a shaft portion (154), a throat portion (156), a blade portion (158) and tip portion (160). The shaft portion (154) has a first end (162) having a first width (164), a first side (166) and a second side (168). The first side (166) and said second side (168) are parallel and the first end (162) is disposed perpendicular between the first side (166) and the second side (168). The throat portion (156) has a third side (170) and a fourth side (172). The third and fourth

## MARKED UP SPECIFICATION

sides have a concave shape to them with a radius of about 2.2 inches. The blade portion (158) has a fifth side (174) and a sixth side (176). The convex portions of the fifth and sixth sides have a radius of about 2.5 inches. The tip portion (160) is linear and disposed between the fifth side and the sixth side, perpendicular to the longitudinal axis (152) and parallel to said first end (162). The tip portion (160) is about 6.75 inches wide and the opposite first end (162) is about 1.87 inches wide. The first control member has a length of about 8.5 inches. The first control member is manufactured from aluminum or stainless steel having a suitable gauge or other suitable material.

Still referring to Figure 6 13, the first control member (150) has an aperture (178) located adjacent to the first end (162) and upon the longitudinal axis (152). The aperture (178) is about 0.50 inches in diameter and adapted to receive the guide sleeve (302) ~~as previously noted~~. Referring back to Figure 11, the The guide sleeve (302) is slotted at ~~(304)~~ 307 to receive ~~projections (309) and (310)~~ the lugs 305 located on the pin member (300). The guide sleeve extends about 1.38 inches above the first control member (150) and about 0.50 inches below the control member (150). The blade portion (158) includes a first elongate aperture (180) having a first aperture longitudinal axis (182). ~~The first aperture longitudinal axis (182) has a first acclivity (184) of about negative 45 degrees from the first control member longitudinal axis (152).~~ The first elongate aperture (180) is located close to the fifth side (174) of the blade portion (158). There is a second elongate aperture (186) having a second aperture longitudinal axis (188). The longitudinal axis (182) and the longitudinal axis (188) are at right angles to each other. ~~having a second acclivity (190) of about positive 45 degrees from the first control member longitudinal axis (152).~~ The second elongate aperture (186) is located close to the sixth side (176) of the blade portion (158). While the first control member described herein constitutes the preferred embodiment of this member, it can take

## MARKED UP SPECIFICATION

other shapes. The first and second elongate apertures are adapted to permit axial alignment of the first and second control members along their respective longitudinal axis.

Referring back to Figure 3 9, the first control member (150) is mounted underneath the swivel seat  
5 ~~body~~ (44) adjacent to bottom surface (81). Elongate apertures (180) and (186) are mounted to the  
bottom surface (81) of swivel seat ~~body~~ (44) ~~as shown~~ so that the ~~first~~ second end (162 153)  
projects beyond the swivel seat ~~body~~ (44) permitting the operator to access the pin (300). The first  
rectangular upper mounting surface (108) of the ~~first~~ second swivel body (92) is mounted below  
the first control member (150) ~~as illustrated in Figure 3~~. Shims (107) having a thickness equal to  
10 the thickness of the first control member are inserted opposite ~~the tip (160)~~ of the first control  
member (150) so that the control member is maintained parallel to the surface (81). The elongate  
apertures (180) and (186) are adapted to permit axial adjustment of the first control member (150)  
with respect to the second control member (200) during installation.

15 Referring now to Figure 7 14, there is shown ~~a variety of views~~ a top view (A) and a side view (B)  
of the second control member (200). The second control member (200) comprises a second flat  
plate having a second flat plate longitudinal axis (202), a top surface (204) and a bottom surface  
(206). The second control member has a substantially keystone shape including a flat bottom side  
(208), a lower left corner (210), a lower right corner (212), an arcuate top side (214), a top left  
20 corner (216), a top right corner (218), a left side (220) inclined away from the second flat plate  
horizontal axis (202) and a right side (222) inclined away from the second flat plate horizontal axis  
(202). The second control member (200) further includes a first elongate aperture (224) located  
proximate to the lower left corner (210). There is also a second elongate aperture (226) located  
proximate to said lower right corner (212). There is a third aperture (228) located proximate to

## MARKED UP SPECIFICATION

said left side. The third aperture has a raised collar (230). A fourth aperture (232) is located adjacent to the third aperture (228) and proximate to the left side (220). The fourth aperture has a raised collar (234). There is also a fifth elongate aperture (240) located proximate to the top left corner (216) and a sixth elongate aperture (242) located proximate to said top right corner (218).

- 5 A seventh aperture (244) is located at the top end of the longitudinal axis (202) and has a raised collar (246). The second control member (200) is manufactured from aluminum or stainless steel having a suitable gauge or other suitable material. The width of bottom side (208) is about 7 inches and the width across the top side (214) is about 9.2 inches. The second control member (200) has a length of about 8 inches. Each of the two bottom elongate apertures (224) and (226)
- 10 are inclined at an angle of about 45 degrees away from the longitudinal axis (202).

- Still referring to Figure 7 14, the second control plate (200) further includes a first rectangular projection (250) projecting from the top left corner (216) of the control plate (200), a second rectangular projection (252) projecting from the middle of the arcuate top surface (214) along the
- 15 control plate longitudinal axis (202) and a third rectangular projection (254) projecting from the top right corner (218) of the control plate (200). The first, second and third rectangular projections are adapted as sighting guides so that an operator can visually guide the third control member (300) into engagement with the second control member (200).

- 20 Referring back to Figure-3 9, the second control member (200) is mounted by mounting means through apertures (224) and (226) between the bottom ~~rectangular~~ member (104) of the ~~first~~ second swivel body (92) and the top ~~rectangular~~ member (98) of the ~~second~~ first swivel body (90). The top curved end (214) of the second control member (200) projects out from under the swivel seat ~~body~~ (44) so that the engagement end (3096) of pin member (300) is able to engage one of the



## MARKED UP SPECIFICATION

three the pin engagement apertures of the second control member (200). The pin engagement apertures on the second control member comprise apertures (244), (240) and (242).

Referring now to Figure & 15, there is shown the operating relationship between the first control member (150), the second control member (200) and the pin member (300). The view in Figure & 15 is with the swivel seat body (44) removed and looking down onto the top ~~rectangular~~ mounting member (98) of the ~~first~~ second swivel body (~~90~~ 92). Note that the elongate apertures (180) and (186) in the first control member (150) and the elongate apertures (224) and (226) (not shown) permit axial adjustment of the first control member (150) with respect to the second control member (200) so that the longitudinal axis (152) of the first control member (150) is aligned with the longitudinal axis (202) of the second control member (200) during initial installation. The initial orientation of control member (150) and control member (200) is shown in Figure & 15 with respect to the bow (16) and stern (18) of the craft. The two control members project to ~~port~~ the left (20). In the configuration shown in Figure & 15, the swivel seat body is oriented so that the operator sitting in the swivel seat body is facing towards the bow (16). The pin member (300) is engaged in a first engagement location with aperture (244) on the second control member (200) thereby fixing the swivel seat body (44) in a bow facing orientation. Referring back to Figure & 9, with pin member (300) engaged within aperture (244) swivel body (92) cannot swivel and swivel body (90) can swivel so that swivel seat body (44) can swivel with respect to the cross-member (34). Referring again to Figure & 15, the operator may wish to fix the swivel seat body in an orientation that permits the operator to face towards the ~~starboard~~ right side (22) of the craft. To do this, the pin member (300) is lifted and disengaged from aperture (244) and the seat is swiveled (~~per arrow (400)~~ to a position that is about 30 degrees to ~~starboard~~ right. The pin member is engaged in a second engagement location into aperture (240). Similarly, if the operator wishes to

## MARKED UP SPECIFICATION

swivel the swivel seat body 30 degrees to ~~port left~~ (per arrow (402)), the pin member (300) can be engaged in a third engagement location into aperture (242).

Referring ~~back now~~ to Figures 1 to 4 and to Figure 16 and also to Figure 9, I will now describe the  
5 ~~means (50) for transmitting~~ means for transmitting body motion commands from the swivel seat  
body (44) to an the outboard motor (26). In Figure 16, there are shown three views (A, B and C)  
of is a control rod connecting member (51) having a first threaded end (450) and a second threaded  
end (452). There is also ~~means~~ a first bracket (454) for connecting the control rod connecting  
member (51) first threaded end (450) to the second control plate (200) and means a second bracket  
10 (456) (identical to the first bracket illustrated in Figure 17) for connecting the connecting member  
(51) second threaded (452) end to the outboard motor (26).

Referring now to Figure ~~10~~ 17, there is ~~are~~ shown multiple views (side, A; top B; and perspective  
C) of means one embodiment of the bracket (454) for connecting the control rod first end (450) to  
15 the second control plate (200). ~~Means Bracket (454) includes elevis (460) comprising~~ comprises a  
base (462) having a threaded aperture (464) adapted to receive the control rod connecting member  
first threaded ends (450) and (452). There is also a first tine (466) fixed to the base (462). The  
first tine has a first arcuate free end (468) and a first tine first aperture (470). There is also a  
second tine (472) fixed to the base (462) opposite to and parallel to the first tine (466). The second  
20 tine has a second arcuate free end (474) and a second tine second aperture (476).

Referring to ~~Figure 10, Figure 11, Figure 12 and Figure 7~~, Figure 18, the elevis there is illustrated  
first means for connecting the connecting member first threaded end to the second control  
member. ~~Bracket (460~~ 454) is adapted to receive the left side of the control plate (200) between

## MARKED UP SPECIFICATION

the first and second tines. The first tine first aperture (470) and the second tine second aperture (476) are co-axially aligned with the control plate third aperture (228) or alternatively control plate fourth aperture (232). A pin member (480) adapted for quick releasable placement within the co-axially aligned first tine first aperture, second tine second aperture and control plate third aperture  
5 is inserted thereby fixing the ~~control rod~~ connecting member (51) ~~first end (450)~~ to the second control plate.

Referring to Figure 13 19, there is illustrated second means for connecting the connecting member threaded second end to the outboard motor (26). ~~I will now describe means (54) for connecting~~  
10 ~~the control rod (51) second end (452) to the outboard motor (26).~~ There is a second elevis bracket (490 456) ~~identical to the first elevis (460)~~ comprising a second base (492) having a second threaded aperture (494) adapted to receive ~~the control rod~~ connecting member ~~second threaded end (452).~~ There is a third tine (496) fixed to the second base with an arcuate free end and an aperture. There is a fourth tine (498) fixed to the second base opposite to and parallel to the third tine. The  
15 fourth tine has a fourth arcuate free end with a fourth tine fourth aperture.

Since both ends of the ~~control rod~~ connecting member (51) are threaded into ~~the first and second elevis (460) and (490) respectively~~ a bracket the tension in the rod can be adjusted by threading more or less of the threaded ends of the rod into the ~~first and second elevis.~~ bracket. As well, the  
20 rod has a contoured shape to permit transmission of movements from the swivel seat ~~body~~ (44) to the outboard motor (26) in an off-set manner.

Referring to Figure 13 19 and Figure 14 20, there is shown a bracket arm (500) having a longitudinal axis (502), a first half (504) and a second half (506). The first half has at least two

## MARKED UP SPECIFICATION

apertures (508 512) and (510 514) positioned vertically. The second half has at least two apertures (512-508) and (514 510) positioned vertically. There is also one threaded longitudinal bore (516) adapted to receive threaded rod (520). Friction clamp (522) is adapted to clamp around the vertical shaft casing (524) of the outboard motor (26). The friction clamp (522) has a collar  
5 portion (526) adapted to frictionally engage the vertical shaft casing and two adjacent and parallel arms (528) and (530 not shown) apertured to receive threaded rod (520). There is a nut (532) adapted for threaded engagement onto the threaded rod so that the two adjacent and parallel arms are between the nut and the bracket second end. When the nut is rotated towards the bracket  
10 second end the two adjacent and parallel arms are compressed together thereby tightening the collar about the vertical shaft casing. A quick release pin (540) is provided for pinning the bracket first end between the third tine and the fourth tine in a pivoting engagement.

Referring back to Figure 3 and Figure 1 9, when the swivel motion of the swivel seat body (44) is fixed with respect to the swivel motion of the control plate (200), arm (600) is used to control the  
15 direction of the swivel seat body and as well the movement of the outboard motor. Arm (600) comprises shaft (602) having a first end (604) and a second end (606). Attached to the second end (606) is hand control knob (608) used by the operator to push the shaft bow ward or stern ward. The first end (604) is placed into shaft receiver (610) welded to the bottom surface of control member (200).

20 Referring now to Figure 15 21, there is shown a schematic diagram of the operation of my invention with the pin member (300) disengaged from control member (200). When the pin member (300) is disengaged from control member (200) first swivel body (90) and second swivel body (92) are free to swivel with respect to each other. Therefore, swivel seat body (44) is free to

## MARKED UP SPECIFICATION

swivel in any direction and cannot be used to direct the boat. The body motion steering control apparatus is disengaged. The arm (600) can be used to direct the craft in a desired direction or alternatively, the operator can swivel the swivel seat body towards the stern and control the direction of the boat using the arm (25) of the outboard motor (26). ~~In Figure 14A if~~ If the  
5 operator wishes the boat to go to ~~starboard~~ the left the arm (600) is moved towards the bow (16) of the boat. This motion is transmitted by ~~control rod~~ connecting member (51) in a pulling motion as indicated by arrows (700) side and the outboard motor (26) is turned so that the propeller (710) swings to ~~starboard~~ the left pushing the bow of the boat to ~~starboard~~ the left. ~~In Figure 14B, if~~ If  
the operator wishes the boat to go to ~~port~~ right the arm (600) is moved towards the stern (18). The  
10 motion is transmitted by ~~control rod~~ connecting member (51) as a pushing motion as indicated by arrows (714 730) and the propeller is forced to ~~port~~ the right. The bow is then driven to ~~port~~ the right.

Referring now to Figure ~~16~~ 22, the control pin (300) is engaged with control member (200). When  
15 the control pin is engaged the body motion steering control apparatus is engaged. First swivel body (90) is fixed and second swivel body (92) ~~are not~~ is permitted independent rotational movement. Therefore, only the swivel seat body (44) may swivel with respect to mounting member (934). The swivel seat body (44) can be used by the operator to impart motion to the propeller in order to direct the boat. In Figure ~~15A~~ 22, if the operator swivels the seat to ~~starboard~~  
20 the right the swivel motion is transmitted by ~~control rod~~ connecting member (51) to the motor as a ~~pulling~~ pushing motion as indicated by arrows (~~730~~ 734). This ~~pulling~~ pushing motion causes the propeller (~~710~~) on the motor (26) to turn to ~~starboard~~ the right as shown by arrow (~~732~~ 6) pushing the bow of the boat to ~~starboard~~ the right. If the operator wishes the boat to move to ~~port~~ the left, the operator swivels the swivel seat body to ~~port~~ the left this causes a ~~pushing~~ pulling motion in

## MARKED UP SPECIFICATION

~~control rod~~ connecting member (51) as indicated by arrows (734 830) causing ~~the propeller (710)~~ to move to ~~port~~ the left as indicated by arrow (7362). This pushes the bow to ~~port~~ the left.

By using the swivel seat body, the operator is able to troll at low speeds while fishing and use

5 body motion to swivel the seat to ~~port~~ the left or ~~starboard~~ the right in order to direct the boat.

This is a preferred hands free operation allowing the operator to concentrate on the sport. As

previously noted, the operator can lock the swivel seat body 30 degrees to ~~port~~ the left or ~~starboard~~

the right permitting the operator to face the desired side of the boat while using body motion to steer the boat.

10

Other embodiments of my invention are contemplated. For example, the arm (600) and shaft

receiver (610) shown on Figure 40 9 may be a single piece of solid, half inch round aluminum rod, welded to the control member (200).

15 In another embodiment of the invention, the first control member (150) can have the same dimensions as the second control member.

In still another embodiment of my invention, an optional bracket can be attached to the swivel seat

~~body~~ (44) having control means to control the operation of the motor, such as start-stop and

20 throttle.

## MARKED UP SPECIFICATION

Although this description has much specificity, these should not be construed as limiting the scope of the invention but as merely providing illustrations of some of the presently preferred embodiments of this invention. Thus the scope of the invention should be determined by the

5 appended claims and their legal equivalents, rather than by the examples given.



MARKED UP SECIFICATION

ABSTRACT

~~The invention is an~~ An apparatus for ~~body motion~~ steering control ~~for of~~ water craft ~~by operator~~  
body motion commands. The craft is powered by an outboard motor having a first vertical  
5 axis. A The water craft has a swivel seat is co-axially mounted to a first and second swivel  
body bodies permitting rotation of the seat about a ~~first~~ second vertical axis. There is a  
first control member ~~is mounted to~~ between the seat and the first swivel body and ~~there is a~~  
second control member is mounted between ~~and to~~ the first and second swivel bodies. A  
connecting member connects the second control member to the outboard motor so that  
10 when a pin couples the first and second control members together the apparatus is engaged  
and swivel seat is able to transmit body motion steering commands via the connecting  
member to the outboard motor. ~~sliding pin is mounted in a sleeve to the first control~~  
~~member. The pin is able to engage the second control member thereby stopping rotation~~  
~~between the first and second swivels. There is a rod between the second control member~~  
15 ~~and the outboard motor. When the pin is engaged into the second control member, the~~  
~~rotation of the seat is directed into the second control member. As the seat rotates, the rod~~  
~~member is able to pull or push one side of the outboard motor thereby transmitting steering~~  
~~commands to the outboard motor.~~